

**Specifications**

SSR - __ D A	Input DCV / Output ACV	Diagram
Load Current (A)	10 15 25 40 50 60 75 90	
Load Voltage (V)	24 - 380 VAC.	
Control Voltage (V)	3 - 32 VDC.	
Control Current (mA)	DC 3 - 25 mA.	
On Voltage (V)	< 1.5 V.	
Off Leakage Current (mA)	< 2.0 mA.	
On - Off Time (mS)	< 10 mS.	
Dielectric Strength (VAC)	2500 VAC.	
Insulation Resistance	1000 M.Ohm / 500 VDC.	
Ambient Temperature (Deg.C)	-30 / +75 Deg.C.	
Indicator LED	Yes	
Size mm. (W x L x H)	45 x 62 x 23.50	
Weight (g)	132 g.	



SSR - __ A A	Input ACV / Output ACV	Diagram
Load Current (A)	10 15 25 40 50 60 75 90	
Load Voltage (V)	24 - 380 VAC.	
Control Voltage (V)	80 - 250 VAC.	
Control Current (mA)	AC < 12 mA.	
On Voltage (V)	< 1.5 V.	
Off Leakage Current (mA)	< 4.0 mA.	
On - Off Time (mS)	< 10 mS.	
Dielectric Strength (VAC)	2500 VAC.	
Insulation Resistance	1000 M.Ohm / 500 VDC.	
Ambient Temperature (Deg.C)	-30 / +75 Deg.C.	
Indicator LED	Yes	
Size mm. (W x L x H)	45 x 62 x 23.50	
Weight (g)	132 g.	



SSR - __ V A	Input VR / Output ACV	Diagram
Load Current (A)	10 15 25 40 50 60 75 80	
Load Voltage (V)	24 - 380 VAC.	
Variable Resistor (K.Ohm)	110VAC= 250K / 220VAC= 500K	
On Voltage (V)	< 1.5 V.	
Off Leakage Current (mA)	< 2.0 mA.	
Dielectric Strength (VAC)	2500 VAC.	
Insulation Resistance	1000 M.Ohm / 500 VDC.	
Ambient Temperature (Deg.C)	-30 / +75 Deg.C.	
Indicator LED	No	
Size mm. (W x L x H)	45 x 62 x 23.50	
Weight (g)	132 g.	



SSR - __ D D	Input DCV / Output DCV	Diagram
Load Current (A)	10 25 40 50	
Load Voltage (VDC)	60, 110, 250 VDC.	
Control Voltage (VDC)	3 - 32 VDC.	
Control Current (mA)	DC 5 - 50 mA.	
On Voltage (V)	< 1.5 V.	
Off Leakage Current (mA)	< 2.0 mA.	
On - Off Time (mS)	< 10 mS.	
Dielectric Strength (VAC)	2500 VAC.	
Insulation Resistance	500 M.Ohm / 500 VDC.	
Ambient Temperature (Deg.C)	-30 / +75 Deg.C.	
Indicator LED	Yes	
Size mm. (W x L x H)	45 x 62 x 23.5	
Weight (g)	132 g.	